

**SEALS
LEAKS**

Asphalt Can't

ROOFS • GUTTERS • VENTS • FLASHINGS • LIGHTS

sticks to
WET
surfaces

SEALS EVERYTHING THAT GOES
Through the ROOF!
Seals Leaks Asphalt Can't



SEALS EVERYTHING THAT GOES

Through the ROOF!

Seals Leaks Asphalt Can't

SEALS LEAKS *Asphalt Can't*

When there's a nagging roof leak that others can't fix, or when you don't want to take your chances, use **Through the Roof!**® Its unique co-polymer rubber formula creates a permanent, invisible seal, even when applied in the middle of a rain storm. (It works great on dry surfaces, too). Through the Roof! will stick to almost any roofing surface – metal, plastic, asphalt, wood, concrete, and more. Plus, it won't freeze. So go ahead and fix that gutter in a Minnesota winter. You might get some concerned stares from your neighbors, but they'll be grateful the next time you host the neighborhood party and their heads stay dry.



Features & Benefits

- ✓ Superior bond durability
- ✓ Humidity & rain proof
- ✓ All-weather formula
- ✓ Sticks to wet surfaces
- ✓ Excellent UV resistance
- ✓ Brush-on formula (available in Qt. or Gallon sizes)
- ✓ Crystal Clear * 19 times clearer than silicone
- ✓ Gunnable down to 0°F
- ✓ Sticks to difficult surfaces
- ✓ Super Elastic – 600% maximum stretch
- ✓ Permanently flexible
- ✓ Strong tear resistance
- ✓ Dripless plunger
- ✓ Freeze-thaw stable in package
- ✓ Full 10.5oz in every cartridge
- ✓ Does not support mold and mildew growth
- ✓ Paintable

Application Basics

Dry Time

Full cure:

1 week (depending on temperature and humidity)

Paintable:

1-2 days with water-based paint

3-4 weeks with oil-based paint



Clean up / Removal

Tools: Mineral spirits or paint thinner

Hands: Citrus-based cleaners

Application Range

0° to 140°F

(-18° to 60°C)

Service Range

-30° to 200°F

(-34° to 93°C)



Description	Item #
10.5 OZ. Black	14060
10.5 OZ. Black - VOC	14065
10.5 OZ. White	14030
10.5 OZ. White - VOC	14035
10.5 OZ. Clear	14010

Description	Item #
Cobra 6-Pack	14026
1 Quart Clear	14003
1 Quart can Clear - VOC	14023
1 Gallon pail Clear	14004
1 Gallon pail Clear - VOC	14024

Where to Use

For repairs that stick, but won't stick out, use Through the Roof! on common roofing fixtures, including:

Metal

- Roofs
- Vents
- Gutters
- Flashing
- Aluminum
- Brass
- Copper
- Galvanized Steel
- Powder-coated metals
- Steel

Other Roof Surfaces

- Acrylic & Polycarbonate Skylights

- Brick
- Asphalt
- Ceramic tile
- Concrete
- Glass
- Mortar
- Polyisobutylene

Other Surfaces

- Stone
- Stucco
- Terra Cotta
- Tile
- Vinyl
- Wood

Where to NOT Use

Adhesion is poor on the following substrates. A test patch is recommended:

- Aquaseal®*
- Cultured marble
- Kynar®*
- Teflon coatings
- Polypropylene
- Polyethylene
- Silicone
- Waxes
- TPO

Through the Roof! has excellent adhesion on these surfaces, but it can wrinkle them. A test patch is recommended:

- EPDM
- Vulcanized rubber

Through the Roof! dissolves foam insulation. Do not use on:

- Polystyrene foam insulation

**Aquaseal® and Kynar® are registered trademarks of their respective owners.*



COBRA™

Lap Joint Nozzle
Fast & Deadly Accurate




Lap Joints Made Easy

You need a flat caulk bead, you have a round nozzle. How does that make sense? That's what we thought. We bring you the right tool, the Cobra Nozzle™. It extrudes a wide bead to easily cover all kinds of lap joints, like roof flashing and window fins, and sandwich joints like thresholds. It comes with a 6-pack of Through the Roof!® clear sealant, well-known for fixing and preventing leaks. Together they help you do your best work. Your customers will think so too.

Alyster Plunger

10.5 oz. cartridges feature Sashco's unique Alyster plunger. A flexible telescopic diaphragm not only stops material flow, it actually pulls material back into the nozzle!

- **Tight Seal** – Increases shelf life and minimizes leakage.
- **Stop Flow** – The flexible telescopic diaphragm assures that material flow will stop when caulk gun pressure is released.



PROPERTY	VALUE
Colors	Clear (All Sizes); Black, White 10.5 OZ. only
Packaging	10.5 OZ. plastic cartridge, 1 quart and 1 gallon containers
Paintability	With latex paint/stain in 1-2 days or oil-based paint/stain after 3-4 weeks
Joint Size	Cartridge — up to 2" wide; Brush grade - N/A
Clarity (NTU)	< 15
Application Range	0°F to 140°F (-18°C to 60°C) surface temp.
Service Range	-30°F to 200°F (-34°C to 93°C)
Tensile Properties	Cartridge – Recovery at 50% stretch: 96% in 1 minute at 100% stretch: 96% in 1 minute Brush – Recovery at 50% stretch: 100% in 3 minutes at 100% stretch: 96% in 5 minutes
VOC	Sashco has VOC compliant Through the Roof products for each region of the country. Exception: 10.5 OZ cartridges of Through the Roof colors are not available in California Contact Customer Service with questions.
Shelf Life	5 years

TEST DATA:

PROPERTY	RESULTS	TEST METHOD
Hardness, Shore A (21-day cure)	Cartridge - 35 Brush - 33	ASTM C661
Slump	Cartridge - < 1/8" Brush - slumps	ASTM D2202
Solids	Cartridge: 57.8% by wt. Brush: 36.0% by wt. Brush lower VOC: 45.4% by wt. Cartridge lower VOC: 53.1% by wt.	ASTM C1250
Extrusion Rate	Cartridge - 80 g/min (1/8" orifice at 40 psi) Brush grade - N/A	ASTM C603
Cured	1 week (dependent on temperature, humidity and bead size/thickness)	ASTM C679
Tack-free	30 minutes	ASTM C679
Low Temp. Flexibility	Pass	ASTM C734
Freeze-Thaw Stable	Won't freeze	ASTM C731
Adhesion-in-peel Passing Substrates	See "ADHERES TO" section	ASTM C794

SPECIFICATIONS:

- Meets FHA requirements.

The data reported here are believed to be reliable. No warranty is made concerning their accuracy or the results obtained from their use.

800-767-5656
sashco.com

Keep up with Sashcoinc on:

TRFBROCH

