## Introducing CENII



# THE ULTIMATE FASTENERS

**EXTERIOR** 

TRIM HEAD SCREW

### EPC\*

DrJ TER 2212-01
Technical Evaluation
Report
available now at

www.screw-products.com



#### **Advanced Trim Head**

The Epic Trim Head is slightly larger in diameter than industry standards. This combined with the patented <sup>(1)</sup> Turbine Ribs give maximum holding power while leaving a clean, professional finish.



Patented<sup>(1)</sup> Turbine Ribs cut quickly into the wood, leaving a professional, clean finish with maximum wood contact. The cup shaped, countersinking head provides increased holding power and reduced risk of splitting.

#### Twin Blades™

Patented<sup>(2)</sup> Twin Blades knurls cut fast to dramatically reduce friction and heat on the shank, while reducing load on the drill. They also provide better performance by removing debris faster than a standard fastener's knurl.

THE RESERVE

#### **Fast Start Tip**

With sharp threads all the way to the tip, the fastener has an immediate grip for a fast start. The inset thread cut drastically reduces the splitting effect and minimizes the driving torque needed to engage the wood.

The advanced Trim Head Wood Screw with ZYTEC™XT corrosion protection coating for exterior environments.

Great for any size job or project.



Available in 1lb, 5lb and 1/4 Keg All Packaging Includes Drive Bit!

**FOLLOW US** 

#### WWW.SCREW-PRODUCTS.COM

Gig Harbor, WA • Bradenton, FL Toll-Free 1-877-844-8880



The EPIC™ Trim Head Screw is designed to take wood screws to an entire new level. Our extra sharp Fast Start Tip saves you time onsite and our Twin Blades™ outperform the competitor's knurls. The Self-Tapping Thread cuts effectively through materials such as wood, plastic and sheet metal. The Turbine Ribs™ ensure an incredibly clean finish. Its cup shaped, countersinking head provides unparalleled holding power and less risk of splitting. The small trim head provides a clean, professional connection.












#### **TYPICAL EXTERIOR USE**

**ZYTEC™XT Coating:** Tested and recognized for use in most ground contact pressure treated lumber for general exterior construction as described by the American Wood Protection Association (AWPA) U1 UC4A or below. Always follow timber manufacturer's recommendations for fasteners.

#### **Common Applications**

- Commercial & residential
- General indoor and outdoor jobs
- Trim & Cabinetry
- Framing
- Windows and doors
- · Remodeling and repair
- And much more!



General I	nfo		
Type of Screw		Trim Head Wood Screw	
Material		Heat Treated, Hardened Steel	
Coating		ZYTEC™ XT	
Head Style		Countersinking TX20 Star Drive	
Point Type		Modified Type 17	
Construction			#9
Head diameter (inch)			0.260
Minor thread diameter			0.122
Major thread diameter			0.183
Shaft diameter			0.136
Drive Size			TX20
Product Range			Approx Count per 1lb
Length	Thread		#9
1-5/8"	1"		148
2"	1-1/4"		122
2-1/2"	1-1/2"		98
3"	1-1/2"		82
4"	2"		61
5"	2-1/2"		50
Also Available with White Painted Head			







Gig Harbor, WA • Bradenton, FL Toll-Free 1-877-844-8880