



GetXed™ Batter Board System

General Information

You have purchased a GetXed™ Batter Board System . his product is designed to make foundation layout faster, require fewer labor hours, and be easier and more economical.

1 Laser Target Bracket

1 Laser Mount Triangle Bracket

15 Triangle Brackets (8 with a cutout on one side; 7 with full sides)

8 Square Slide Brackets

54 Wing Nuts

Tri pod Screw



Instructions for Use:

Set up all four corner T-posts approximately 38 inches apart Center-to-center unless otherwise required by your layout style Make sure the knobs on the T-Posts are facing each other and square with each other. When placing the brackets on the T-Post, it is best to work inside the pad.

- 1 Start with Triangle Laser mount Bracket: Place on the right-hand side with the wing nuts facing you. Slide down and tighten wing nuts.
- 2 Place Square Slide Bracket on 2 x2 board. With the String Line hook facing up and the wing nut facing you. Slide the 2x2 into the Triangle Laser mount bracket.
- 3 Grab a Triangle Bracket with the cut out. Place on the T-Post with the cut out on the bottom and the wing nuts facing towards you. Visually align the bracket so it is close to the height of the first bracket. Slide the 2x2 into the bracket. Hand tighten the wing nuts. From here you can either put a level on the 2x2 or use your laser to get the correct height on the brackets.
Always make sure you level this corner first. Once the height is set, always make adjustments on the triangle brackets — not the laser bracket.
- 4 You will do this for all four corners.
- 5 Once all four corners are set you can attach the string line to the Square Slide Bracket and then pull your measurements and make the adjustment by sliding the bracket to the desired location to get your X.

Items needed to be purchased separately:

- 16 - T-Posts and T Post Pounder (can be purchased at most Tractor Supply, Lowes, Home Depot or construction supply companies. Various lengths can be used depending on your situation)
- T-post puller optional but makes removing T-Post easier
- 8 - 2x2 posts approximately 36 inches long
- Laser
- String line

PRODUCT SAFETY GUIDELINES

Read and understand all safety instructions before use.

Failure to follow these safety guidelines may result in serious injury, death, or damage to equipment. This product is designed for construction layout use only and must be used as intended.

WARNING – EYE & FACE PROTECTION

Always wear ANSI-approved eye protection when installing or using this product.

CAUTION – HEARING PROTECTION

Wear hearing protection when operating power tools during layout activities.

WARNING – FOOTWEAR REQUIRED

Always wear substantial footwear, such as steel-toe or reinforced work boots with slip-resistant soles. Failure

to wear proper footwear may result in severe injury to feet.

WARNING – UNDERGROUND UTILITIES (CALL 811)

Always locate underground utilities before driving stakes or drilling. Call 811 or your local utility service.

Failure to do so may result in serious injury or death.

WARNING – SHARP EDGES

This product may contain sharp edges that can cause cuts or lacerations.

Always wear appropriate protective gloves when handling, assembling, or installing this product.

■ **WARNING** – CALIFORNIA PROPOSITION 65

 **WARNING:** This product can expose you to chemicals, including substances that are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

LIMITED WARRANTY

This product carries a limited warranty to the original purchaser, covering defects in materials and workmanship only. At our discretion, we will repair or replace the product or any defective part(s).

This warranty does not apply to product failure or defects resulting from normal wear and tear, direct or indirect misuse, abuse, negligence, accidents, alteration, unauthorized repairs, or lack of proper maintenance.

Items must be shipped prepaid to our Mount Pleasant, South Carolina location. If a product must be returned for warranty service, please contact us to obtain a Return Goods Authorization (RGA) number and further instructions. Returns without an RGA number may be refused.

LIMITATION OF LIABILITY

This warranty is the sole and exclusive warranty provided. We disclaim all other express or implied warranties, including any implied warranties of merchantability or fitness for a particular purpose. In no event shall the manufacturer be liable for incidental, consequential, or indirect damages.

SHIPPING RESPONSIBILITY

The customer is responsible for all inbound shipping costs. Outbound return shipping will be determined at our discretion.

PROOF OF PURCHASE

Proof of original purchase may be required to obtain warranty service.