



SIBAX[®]

CONSTRUCTION | AUTOMOTIVE | INDUSTRIAL CHEMICALS



Wherever
You Need



PRODUCT CATALOGUE | 2026



ABOUT US

Siba was established in 2004 in order to serve in the industries of construction, hardware-fittings, furniture and automotive with its environmentally-friendly and high technology isolation, insulation and adhesive products.

Our management policy; is to create a RELIABLE integrated management system based on the conditions of quality, environment, occupational health and safety management systems and aiming to strengthen the perception of the company. To offer our wide product range to our customers with high quality, to be a reliable company that fully meets the needs of our customers by using up-to-date and developing technology, to be close to the customer and to maintain customer satisfaction with our sales - marketing network. To add value to our customers with the understanding of delivery to the door, to keep our work enthusiasm at the highest level as a team, to be open to continuous development, to produce in accordance with the relevant standards, regulations and customer demands and the expectations of all relevant parties.

OUR FACILITIES

Operating in an outdoor location of 150.000 m² and an indoor location of 50.000 m² in the Organized Industrial Zone, Gümüşova, Düzce, Siba Chemistry manufactures and sells PU. FOAMS, SILICONES, PU. and HYBRID SEALANTS, ADHESIVES, ACRYLIC and SILICONE SEALANTS, SPRAY PAINTS, INDUSTRIAL SPRAYS in a wide range of products with its R&D, production, sales & marketing and management personnel each specialized in their respective fields using the state-of-the-art technology machines and equipment.

Siba is the first integrated facility in the world that is capable of manufacturing its own plastic cartridges using the IML technology.

Siba possesses all the required quality certifications. Adopting an understanding of continuously making investments to meet the requirements of customers in a fast and complete manner providing high quality precision during all the stages of the production, Siba Chemistry serves you, our esteemed customers, with private brands and its own registered brand: Sibax.





KALİP PİRETESİ

SIBAX
POLIÜRETAN KÖPÜK
POLYURETHANE FOAM

SIBAX
POLIÜRETAN KÖPÜK
POLYURETHANE FOAM



SIBAX®

POLYURETHANE FOAMS

POLYURETHANE FOAMS PRODUCT GROUP



- Polyurethane Filling Foam
- Polyurethane Maxi High Yield Foam
- Polyurethane Mega High Yield Gun Foam
- Polyurethane Fixing Foam
- Polyurethane Fire Rated B2 Foam
- Polyurethane Fire Rated B1 Foam
- Polyurethane Door Window Foam
- Polyurethane Gun Foam
- Polyurethane Re-Usable Foam
- Polyurethane Thermal And Acoustic Insulation Foam
- Polyurethane Bonding Foam
- Polyurethane Flexible Gun Foam
- Polyurethane Adhesive Foam
- Polyurethane Foam Cleaner

NS¹³ POLYURETHANE FILLING FOAM



| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 300 ml | 12 | 160 |

NS⁵⁵ POLYURETHANE FILLING FOAM



| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 500 ml | 12 | 160 |

DESCRIPTION

General purpose polyurethane foam.

Properties: Low expansion, does not apply high pressure on application substrates and door frames.

Application Areas: Filling of holes, cracks and gaps in buildings for insulation purposes.

NS⁶⁶ POLYURETHANE FILLING FOAM



| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 600 gr | 12 | 120 |

DESCRIPTION

General purpose polyurethane foam.

Properties: Cures quite fast even eliminating the need of moisturizing the substrates. Excellent cell structure and stability enables effective insulation and no shrinkage.

Application Areas: Filling gaps around window frames. Filling penetration gaps of gas pipes, plumbing, electricity installations. Filling holes, cracks and gaps in buildings for insulation purpose. Mounting applications of panels, air conditioning and air vents.

NS⁷⁰ POLYURETHANE MAXI HIGH YIELD FOAM



| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 1000 gr | 12 | 120 |

DESCRIPTION

High yield and low expansion PU foam formulated for fixing door and window frames.

Properties: High efficiency up to 60 liters. It dries much faster and better than standard straw foams, cell structure. It can be used in four seasons. It does not lose volume. Very strong adhesion to common construction materials. Does not flow on vertical surfaces.

Application Areas: Gaps around door and window frames filling. Around PVC and aluminum joinery. Gap filling applications.

NS⁷² POLYURETHANE MEGA HIGH YIELD GUN FOAM



| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 1000 gr | 12 | 120 |

NS^{72W} POLYURETHANE MEGA HIGH YIELD GUN FOAM WINTER



| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 1000 gr | 12 | 120 |

DESCRIPTION

Gun-grade PU foam formulated for maximum yield in filling and insulating of gaps, cracks and openings in buildings.

Properties: Strong adhesion to most surfaces. Applies low pressure on substrates. Usable in temperatures above +5°C.

Application Areas: Filling and insulating gaps around window frames. Filling and insulating cracks, gaps, and joints in buildings.

NS⁷⁷ POLYURETHANE FIXING FOAM



| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 750 ml | 12 | 120 |

DESCRIPTION

General purpose polyurethane aerosol mounting and filling foam.

Properties: Controlled growth does not exert excessive pressure on the surfaces, does not stretch the muscles. It dries very quickly, eliminating the need for moisturizing. Excellent stability-does not pull. It does not flow on vertical surfaces. It has strong adhesion to building materials.

Application Areas: Fixing of door and window frames to the wall. Filling of holes, cracks and gaps in buildings for insulation purposes. Installation applications for panels, tables, air conditioners, ventilation ducts, etc. In the assembly of PVC and wooden joinery. Bonding and insulation of common building materials.

NS⁸⁰ POLYURETHANE FIRE RATED B2 FOAM



| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 750 ml | 12 | 120 |

DESCRIPTION

B2 class polyurethane foam according to DIN EN 4102 standard, with limited fire resistance, self-extinguishing when withdrawn from the flame source.

Properties: Self-extinguishes when kept away from the source of fire. Meets B2 class according to DIN 4102. Excellent adhesion on wood, metal, glass and concrete. Effective thermal and sound insulation.

Application Areas: Fire-retardant filling and insulating gaps around window and door frames. Insulating electrical boards, ducts etc.

NS⁸² POLYURETHANE FIRE RATED B1 FOAM / NS^{82T} POLYURETHANE FIRE RATED B1 GUN FOAM



| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 900 gr | 12 | 120 |

DESCRIPTION

Polyurethane-based aerosol capable of resisting burning filler and mounting foam.

Properties: Slows growing fire. Does not trigger fire. Meets B1 class according to DIN 4102. Strong adhesion on common construction elements. Excellent sealing against gas and smoke. Red color for easy identification. Excellent adhesion on wood, metal, glass, and concrete. Effective thermal and sound insulation.

Application Areas: Fire-retardant filling and insulating gaps around window and door frames. Insulating electrical boards, ducts etc...

NS⁸⁴ POLYURETHANE DOOR WINDOW FOAM



| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 750 ml | 12 | 120 |

NS^{84T} POLYURETHANE DOOR WINDOW GUN FOAM



| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 750 ml | 12 | 120 |

DESCRIPTION

High expansion / low expansion polyurethane-based aerosol mounting foam with strong adhesion for the installation of indoor and outdoor doors.

Properties: High mechanical properties, carry loads. Controlled expansion does not swell excessively. Shrinkage-free. Cuttable, sandable, paintable.

Application Areas: Fixing door and window frames. In air conditioner installation.



NS^{84W} POLYURETHANE DOOR WINDOW FOAM WINTER



| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 750 ml | 12 | 120 |

NS^{84TW} POLYURETHANE DOOR WINDOW GUN FOAM WINTER



| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 750 ml | 12 | 120 |

DESCRIPTION

High expansion / low expansion polyurethane-based aerosol mounting gun winter foam with strong adhesion for the installation of indoor and outdoor doors.

Properties: Very strong adhesion. High mechanical properties. Controlled expansion. Shrinkage-free. Cuttable, sandable, paintable. Resistant up to -10° C.

Application Areas: Fixing door and window frames. In air conditioner installation.



NS⁸⁸ POLYURETHANE GUN FOAM



| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 750 ml | 12 | 120 |

DESCRIPTION

High efficiency polyurethane gun foam for professional users, which can be easily dosed with the application gun. **Properties:** High yield foam allows to fill higher number of doors and windows. Controlled expansion, low pressure on door and window frames. Cures fast, becomes cuttable within half an hour. High stability, no shrinkage. Non-sag on vertical substrates. Re-usable if the applicator gun left on the can. Strong adhesion on common building materials.

Application Areas: Filling and insulating gaps around window and door frames. Filling penetration gaps of pipes belonging to gas, water, electricity etc. installations. Filling and insulating irregular gaps, cracks and holes in buildings.



NS⁹⁰ POLYURETHANE RE-USABLE FOAM



| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 750 ml | 12 | 120 |

DESCRIPTION

Extra high efficiency foam with patented mechanical valve that can be used repeatedly without the risk of clogging. **Properties:** After the first use, the foam can be applied repeatedly without blocking the valve. It dries quickly, cures easily even at low temperatures and in environments where there is not enough humidity. Its narrow pipette provides high efficiency. Strong adhesion to common building materials. It provides effective sound and heat insulation.

Application Areas: Filling gaps surrounding door and window frames. Filling penetration gaps of pipes belonging to gas, water, electricity etc. installations. Filling of holes, cracks and gaps in buildings for insulation purposes.



NS⁹⁴ POLYURETHANE THERMAL AND ACOUSTIC INSULATION FOAM / NS^{84T} POLYURETHANE THERMAL AND ACOUSTIC INSULATION GUN FOAM



| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 750 ml | 12 | 120 |

DESCRIPTION

One-component, polyurethane-based heat and sound insulation foam with gun, and straw applied by spraying method. **Properties:** Based on polyurethane: effective heat and sound insulation. Excellent adhesion: Very strong adhesion to common building materials. Practical: easy to apply without skill, no mechanical fixing required. **Application Areas:** Indoor and outdoor walls. Roofs and attics. Building foundations and basements. Pipes and channels. Containers, vehicle bodies and trailers. Hot water tanks.

NS⁹⁶ POLYURETHANE BONDING FOAM



| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 750 ml | 12 | 120 |

NS^{96T} POLYURETHANE BONDING GUN FOAM



| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 750 ml | 12 | 120 |

DESCRIPTION

Polyurethane based, bonding foam which has fast initial tack strong adhesion on construction materials.

Properties: Adheres strongly to the surfaces on which it is applied. Provides easy operation thanks to fast curing. Provides the highest performance by providing instant adhesion.

Application Areas: Bonding of thermal insulation boards. Bonding and assembly of wood, concrete, metal, brick, etc. materials.



NS^{98T} POLYURETHANE FLEXIBLE GUN FOAM



| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 750 ml | 12 | 120 |

DESCRIPTION

Flexible polyurethane foam for professional users, easy to dose with an application gun.

Properties: High elastic recovery rate. Shock and impact absorbing feature. Gun application; easier and more controlled dosing. Heat and sound insulation thanks to its high adhesion and filling performance. Does not flow on vertical surfaces.

Application Areas: As a stabilizing foam to create a soundproof layer. For insulation and fixing purposes in door and window frames. Filling joints in roof constructions. Increasing thermal insulation in heating/cooling systems. Insulation of electrical sockets and water pipes.



NS⁹⁹ POLYURETHANE ADHESIVE FOAM



| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 900 gr | 12 | 120 |

NS^{99T} POLYURETHANE ADHESIVE GUN FOAM



| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 900 gr | 12 | 120 |

DESCRIPTION

Adhesive polyurethane foam that can be used in the assembly of sheathing insulation boards on the exterior of buildings. **Properties:** Insulation of the plates assembly speeds up and makes it easier. Buildings heat to isolation contribution it does. A lot annoyed growth-swelling makes. Alternative to adhesives by comparison saving provides. Combustion retarder contribution materials includes.

Application Areas: EPS and XPS insulation boards, buildings external to their fronts gluing and between them of the gaps filling. Polyurethane and stone wool of the panels gluing. Widespread build of materials strong and resistant gluing.



NS²² POLYURETHANE FOAM CLEANER

| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 500 ml | 12 | 120 |



GUN FOAM

| QTY/BOX |
|---------|
| 1 |



DESCRIPTION

Solvent based aerosol foam cleaner. It helps to clean foam guns and pu foams that have not yet fully dried.

SILICONE SEALANTS

SILICONE SEALANT PRODUCT GROUP



- Sanitary Silicone Sealant
- Neutral Sanitary Silicone Sealant
- Insulating Glass Silicone Sealant
- Neutral Mirror Silicone Sealant
- Aquarium Silicone Sealant
- Neutral Construction And Facade Silicone Sealant
- Neutral Marble Silicone Sealant
- Neutral Epdm Membrane Silicone Sealant
- Universal Silicone Sealant
- Neutral Fire Rated B1 Silicone Sealant
- Neutral Gasket Maker Silicone Sealant (Rtv)
- Acetoxy Gasket Maker Silicone Sealant (Rtv)
- Autoglass Adhesive

LS¹⁰ SANITARY SILICONE SEALANT

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|-----------------|--------------------|---------|--------------|
| 280 ml / 310 ml | Transparent, White | 24 | 120 |

DESCRIPTION

100% acetoxy silicone with excellent adhesion, with increased resistance to mold and fungus, for use on wet surfaces.

Properties: Single component, easy to apply. 100% silicone and solvent-free. Prevents mold and fungus formation. Resistant to UV and does not crack or turn yellow. Cures fast and reaches waterproof form within hours. Provides excellent adhesion to many building materials thanks to its high adhesion feature. Resistant to detergents, cleaning materials and chemicals. Provides strong adhesion to non-porous surfaces such as tiles, ceramics, glass.

Application Areas: Wet areas such as bathrooms and kitchens. Sealing around shower cabins, bathtubs, sinks, etc.. Joints of tiles which is open to water contact. Sealing of cold storage units. Sealing in kitchenware and bathroom furniture. Sanitary systems.



LS¹⁴ NEUTRAL SANITARY SILICONE SEALANT

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|--------------------|---------|--------------|
| 300 ml | Transparent, White | 24 | 100 |

DESCRIPTION

Moisture and mildew resistant, neutral cure 100% silicone for use on wet surfaces.

Properties: Neutral cured pure silicone, resistant to moisture and mold, for use on wet surfaces. 100% silicone, solvent free. It does not leave any irritating odor during drying. Very strong adhesion to common construction materials. Contains effective additives that prevent fungus and mold growth. It dries quickly to form a waterproof barrier.

Application Areas: Wet areas such as bathrooms and kitchens. Sealing around shower cabins, bathtubs, sinks, etc.. Joints of tiles which is open to water contact. Sealing of cold storage units. Sealing in kitchenware and bathroom furniture. Sanitary systems.



LS¹⁸ INSULATING GLASS SILICONE SEALANT

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|-------|---------|--------------|
| 600 ml | Black | 20 | 60 |

DESCRIPTION

High quality, single component, elastomeric, neutral curing silicone sealant specifically developed for IG unit manufacturing.

Properties: Does not slump in vertical joints. Excellent adhesion to glass, metal, aluminium and galvanized steel. Solvent-free, no shrinkage. Resistance to weather conditions and UV. Compatible with sealants used in the manufacture of IG glass.

Application Areas: Designed for secondary sealing of IG units, and used together with PIB primary sealant.



LS²² NEUTRAL MIRROR SILICONE SEALANT

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|-------------|---------|--------------|
| 280 ml | Transparent | 24 | 100 |

DESCRIPTION

A fast-drying, neutral silicone-based adhesive designed for mirror bonding applications

Properties: Single component, easy to apply. Resistant to weather conditions and UV. Odorless. Solvent-free, long-lasting. Very fast curing. It provides excellent adhesion to many building materials thanks to its high adhesion feature.

Application Areas: Indoor and outdoor. Fixing all kinds of mirrors. Sealing and bonding applications on acid-sensitive substrates. Join combinations of glass, aluminium and glazed surfaces. Fixing the wall tiles and accessories with glazed surfaces.



LS³⁰ AQUARIUM SILICONE SEALANT

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|--------------------|---------|--------------|
| 280 ml | Transparent, White | 24 | 100 |

DESCRIPTION

Excellent adhesion silicone formulated for aquarium assembly and sealing on glass.
Properties: Single component, easy to apply. 100% silicone and solvent-free. Resistant to UV and does not crack or turn yellow. Cures fast and reaches waterproof form within hours. It provides excellent adhesion to many building materials thanks to its high adhesion feature. Resistant to detergents, cleaning materials and chemicals. Safe to aquarium animals and plants.
Application Areas: Indoor and outdoor. Bonding and sealing aquariums. Bonding of glass elements. Bonding and sealing of glass display windows.

LS³¹ NEUTRAL CONSTRUCTION AND FACADE SILICONE SEALANT (EN 15651-1, EN 15651-2) **CE**

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|---|---------|--------------|
| 600 ml | Transparent, Black, White, Grey, *Other Colors | 20 | 60 |

DESCRIPTION

High quality, weatherproof, flexible neutral silicone used in building and construction joints, indoor and outdoor applications.
Properties: Single component, easy to apply. Resistant to weather conditions and UV. Odorless. Resistant to low and high temperature changes. High elastic. Solvent-free, long-lasting. Not affected from weather conditions when cured. Provides excellent adhesion to many building materials thanks to its high adhesion feature.
Application Areas: All aluminium composite panel joints. For filling and sealing in door and window, sanitary ware, bathroom and kitchen applications. All kind of joints sealing applications in construction. All general sealing applications of concrete, metal, wood, brick and plastic construction elements. Joint combinations of PVC, aluminium and glass. Floor, wall, ceiling joints.

LS³² NEUTRAL CONSTRUCTION AND FACADE SILICONE SEALANT (EN 15651-1, EN 15651-2) **CE**

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|---|---------|--------------|
| 300 ml | Black, White, Grey, Transparent, *Other Colors | 24 | 100 |

DESCRIPTION

High quality, weatherproof, flexible neutral silicone used in building and construction joints, indoor and outdoor applications.
Properties: Single component, easy to apply. Resistant to weather conditions and UV. Odorless. Resistant to low and high temperature changes. High elastic. Solvent-free, long-lasting. Not affected from weather conditions when cured. Provides excellent adhesion to many building materials thanks to its high adhesion feature.
Application Areas: All aluminium composite panel joints. For filling and sealing in door and window, sanitary ware, bathroom and kitchen applications. All kind of joints sealing applications in construction. All general sealing applications of concrete, metal, wood, brick and plastic construction elements. Joint combinations of PVC, aluminium and glass. Floor, wall, ceiling joints.

LS⁵² NEUTRAL MARBLE SILICONE SEALANT

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|-------------|---------|--------------|
| 280 ml | *All Colors | 24 | 100 |

DESCRIPTION

A neutral silicone sealant that does not cause staining or bleeding on natural stone surfaces such as granite and marble. It is free from plasticizers and suitable for both indoor and outdoor applications.
Properties: Contains no organic or inorganic plasticizers that may cause bleeding. Neutral cure; does not cause corrosion. Excellent adhesion to porous substrates such as natural stones. Antibacterial; resistant to moisture and mold. Resistant to weather conditions such as sunlight, wind, and rain.
Application Areas: Expansion joints on natural stone facades. Movement joints between natural stones and other building materials such as wood and metal. Sealing applications on natural stone surfaces in wet areas such as kitchens, bathrooms, and swimming pools.

*The minimum order quantity of Sibax products is 1000 pieces.

LS⁶² NEUTRAL EPDM MEMBRANE SILICONE SEALANT

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|-------|---------|--------------|
| 600 ml | Black | 20 | 60 |

DESCRIPTION

Neutral silicone-based, one-component, elastic EPDM membrane adhesive.
Properties: Single component, easy to apply. Strong adhesion on EPDM membranes and on the common construction materials. Resistant to weather conditions and UV. Odorless. Tolerates all kinds of movements in joints thanks to its high modulus. Solvent-free, long-lasting. Not affected from weather conditions when cured.
Application Areas: Indoor and outdoor. Bonding EPDM membranes to each other. Bonding EPDM membranes and different building surfaces.

LS⁶⁶ UNIVERSAL SILICONE SEALANT (EN 15651-1, EN 15651-2, EN 15651-3) **CE**

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|--|---------|--------------|
| 280 gr | Transparent, White | 24 | 120 |
| 280 gr | Black, Brown, Grey, Anthracite, *Other Colors | 24 | 120 |

DESCRIPTION

It is a one-component acetoxy silicone with strong adhesion, especially to non-porous surfaces such as glass, tiles, ceramics and aluminum for sealing applications.
Properties: Single component, easy to apply. Does not form mold and fungus. Resistant to UV rays and does not crack or turn yellow. Cures fast and reaches waterproof form within hours. Thanks to its high adhesion feature, it provides excellent adhesion to many building materials. Provides strong adhesion to non-porous surfaces such as tiles, ceramics and glass.
Application Areas: Indoor and outdoor. In places with high humidity such as bathrooms and kitchens. Suitable for shower stalls, bathtubs, sinks, etc. for sealing purposes in assembly and around. In the joints of tiles that may come into contact with water.

LS⁷² NEUTRAL FIRE RATED B1 SILICONE SEALANT

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|-------|---------|--------------|
| 310 ml | White | 24 | 100 |

DESCRIPTION

A one-component neutral silicone that forms a fire-resistant, highly mobile sealant when dry.
Properties: Single component, easy to apply. Resistant to fire for 4 hours according to TS EN 1366-4 test method. Resistant to weather conditions and UV. High elastic. Solvent-free, long-lasting. Provides excellent adhesion to many building materials thanks to its high adhesion feature.
Application Areas: Expansion joints. Metal pipes. Door and window joints. Wall, ceiling joints. In electrical cables and installation pipes. Hot/cold water pipes, metal pipes.

LS⁷⁷ UNIVERSAL SILICONE SEALANT (EN 15651-1, EN 15651-2, EN 15651-3) **CE**

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|-----------------------------------|---------|--------------|
| 280 ml | Transparent, White, *Other Colors | 24 | 120 |

DESCRIPTION

One-component silicone sealant, providing a strong adhesion for common building materials like ceramic, aluminium and glass. Used for sealing and glazing applications.
Properties: Single component, easy to apply. Prevents mold and fungus formation. Resistant to UV and does not crack or turn yellow. Cures fast and reaches waterproof form within hours. Provides excellent adhesion to many building materials thanks to its high adhesion feature. Provides strong adhesion to non-porous surfaces such as tiles, ceramics, glass.
Application Areas: Indoor and outdoor. Wet areas such as bathrooms and kitchens. Sealing around shower cabins, bathtubs, sinks, etc.. Joints of tiles which is open to water contact.

*The minimum order quantity of Sibax products is 1000 pieces.

LS78 UNIVERSAL SILICONE SEALANT

(EN 15651-1, EN 15651-2, EN 15651-3) CE

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|-----------------------------------|---------|--------------|
| 600 ml | Transparent, White, *Other Colors | 20 | 60 |

DESCRIPTION

It is a one-component silicone that adheres strongly to non-porous surfaces such as glass, tiles, ceramics and aluminum for sealing and bonding applications.

Properties: Single component, easy to apply. Does not form mold and fungus. Resistant to UV rays and does not crack or turn yellow. Cures fast and reaches waterproof form within hours. Thanks to its high adhesion feature, it provides excellent adhesion to many building materials. Provides strong adhesion to non-porous surfaces such as tiles, ceramics and glass.

Application Areas: Indoor and outdoor. In places with high humidity such as bathrooms and kitchens. Suitable for shower stalls, bathtubs, sinks, etc. for sealing purposes in assembly and around. In the joints of tiles that may come into contact with water.

LS88 UNIVERSAL SILICONE SEALANT

(EN 15651-1, EN 15651-2, EN 15651-3) CE

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|-----------------------------------|---------|--------------|
| 310 ml | Transparent, White, *Other Colors | 24 | 100 |

DESCRIPTION

One-component silicone sealant, providing a strong adhesion for common building materials like ceramic, aluminium, and glass. Used for sealing and glazing applications.

Properties: Single component, easy to apply. Prevents mold and fungus formation. Resistant to UV and does not crack or turn yellow. Cures fast and reaches waterproof form within hours. Provides excellent adhesion to many building materials thanks to its high adhesion feature. Provides strong adhesion to non-porous surfaces such as tiles, ceramics, glass.

Application Areas: Indoor and outdoor. Wet areas such as bathrooms and kitchens. Sealing around shower cabins, bathtubs, sinks, etc.. Joints of tiles which is open to water contact.

LS89 NEUTRAL GASKET MAKER SILICONE SEALANT (RTV)

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|-------------|---------|--------------|
| 280 ml | *All Colors | 24 | 100 |

DESCRIPTION

High performance, neutral cured 100% silicone sealant without solvent additives. Gasket maker which retains its flexibility in temperatures up to 300°C.

Properties: Single component, easy to apply. Oxime silicone, odourless. 100% silicone and solvent-free. Resistant up to +300°C. Cures fast and reaches waterproof form within hours. Improved oil resistance. Provides excellent adhesion to many building materials thanks to its high adhesion feature. Highly elastic and turns to its original form without being distorted.

Application Areas: Places exposed to high temperatures. All applications for constantly exposed to high temperature. Automotive motor components, differential cover, gear-case cover, motor hood and carburettor cover sealing. Steam installations, as sealant in places exposed to hot water and steam. Hot-air pipes. All sealing applications exposed to mechanical or chemical heating.

LS99 ACETOXY GASKET MAKER SILICONE SEALANT (RTV)

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|------------|---------|--------------|
| 280 ml | Red, Black | 24 | 100 |

DESCRIPTION

High performance, acetoxy curing silicone gasket maker which retains its flexibility in temperatures up to 300°C.

Properties: Single component, easy to apply. 100% silicone and solvent-free. Resistant up to +300°C. Cures fast and reaches waterproof form within hours. Provides excellent adhesion to many building materials thanks to its high adhesion feature. Highly elastic and turns to its original form without being distorted.

Application Areas: Places exposed to high temperatures. All applications for constantly exposed to high temperature. Automotive motor components, differential cover, gear-case cover, motor hood and carburettor cover sealing. Steam installations, as sealant in places exposed to hot water and steam. Hot-air pipes. All sealing applications exposed to mechanical or chemical heating.

WS55 AUTOGLASS ADHESIVE

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|-------|---------|--------------|
| 280 ml | Black | 24 | 120 |

WS60 AUTOGLASS ADHESIVE

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|-------|---------|--------------|
| 600 ml | Black | 20 | 60 |

DESCRIPTION

Isocyanate-free neutral cure windshield adhesive which can be applied without primer. Following the application it reacts with the ambient humidity to form high-modulus silicone rubber.

Properties: Excellent adhesion on glass, metal and residual adhesives left from the prior application. Does not require primer and activator. Free of solvents and isocyanates, environmentally friendly. Excellent non-sagging behavior. Highly Resistant to aging, weather conditions and UV. Maintains its adhesion and mechanical properties for long years. Can easily be cleaned without solvent following to the application.

Application Areas: Bonding glass and windscreens in every sort of automotive, trucks, busses and work vehicles.

LS65 UNIVERSAL SILICONE SEALANT

(EN 15651-1, EN 15651-2, EN 15651-3) CE

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|-----------------------|--------------------|---------|--------------|
| 40 ml (Boxed/Blister) | Transparent, White | 36 | 147 |

DESCRIPTION

One-component silicone sealant, providing a strong adhesion for common building materials like ceramic, aluminium, and glass. Used for sealing and glazing applications.

Properties: Single component, easy to apply. Does not form mold and fungus. Resistant to UV rays and does not crack or turn yellow. Cures fast and reaches waterproof form within hours. Thanks to its high adhesion feature, it provides excellent adhesion to many building materials. Provides strong adhesion to non-porous surfaces such as tiles, ceramics and glass.

Application Areas: Indoor and outdoor. Wet areas such as bathrooms and kitchens. Sealing around shower cabins, bathtubs, sinks, etc.. Joints of tiles which is open to water contact.

LS87 NEUTRAL GASKET MAKER SILICONE SEALANT (RTV)

LIQUID GASKET

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|-----------------|------------------|---------|--------------|
| 80 ml (Blister) | Black, Grey, Red | 36 | 120 |

DESCRIPTION

High performance, neutral cured %100 silicone sealant without solvent additives. Gasket maker which retains its flexibility in temperatures up to 300°C.

Properties: Oxime silicone, odourless. 100% silicone and solvent-free. Resistant up to +300°C. Cures fast and reaches waterproof form within hours. Improved oil resistance. Provides excellent adhesion to many building materials thanks to its high adhesion feature.

Application Areas: All applications for constantly exposed to high temperature. Automotive motor components, differential cover, gear-case cover, motor hood and carburettor cover sealing. Steam installations, as sealant in places exposed to hot water and steam. Hot-air pipes.

LS98 ACETOXY GASKET MAKER SILICONE SEALANT (RTV)

LIQUID GASKET

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|------------|---------|--------------|
| 50 ml (Boxed) | Red, Black | 36 | 147 |

DESCRIPTION

High performance, acetoxy cure silicone gasket maker which retains its flexibility in temperatures up to 300°C.

Properties: Single component, easy to apply. 100% silicone and solvent-free. Resistant up to +300°C. Cures fast and reaches waterproof form within hours. Provides excellent adhesion to many building materials thanks to its high adhesion feature. Highly elastic and turns to its original form without being distorted.

Application Areas: Places exposed to high temperatures. All applications for constantly exposed to high temperature. Automotive motor components, differential cover, gear-case cover, motor hood and carburettor cover sealing. Steam installations, as sealant in places exposed to hot water and steam. Hot-air pipes. All sealing applications exposed to mechanical or chemical heating.

*The minimum order quantity of Sibax products is 1000 pieces.

*The minimum order quantity of Sibax products is 1000 pieces.

POLYURETHANE SEALANTS

POLYURETHANE SEALANT PRODUCT GROUP

POLYURETHANE SEALANTS

SB⁹⁰ ULTRA POLYURETHANE SEALANT

(TS EN 15651-1, EN 15651-4) CE

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|--|---------|--------------|
| 280 ml | White, Black, Grey, Anthracite, *Other Colors | 12 / 25 | 216 / 100 |

DESCRIPTION

Polyurethane based, one component, medium hardness general purpose construction and automotive sealant. **Properties:** Single component, easy to apply. Fast-cure. Resistant to weather conditions and UV radiation. Can be overpainted. Does not sag. Permanently elastic. Chemical resistance is high. Becomes waterproof when cured. Excellent adhesion to many building materials.

Application Areas: Indoor and outdoor. All kind of sealing and bonding applications in construction. Assembly and sealing of construction elements such as concrete, metal, wood, PVC, betopan. Assembly and isolation of sandwich panel in roof and facade. In manufacturing applications such as automotive, containers, trucks. Roof and terrace dilatations and in joints of parapet corners.



SB⁹¹ ULTRA POLYURETHANE SEALANT

(TS EN 15651-1, EN 15651-4) CE

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|-----------------------------------|---------|--------------|
| 600 ml | White, Black, Grey, *Other Colors | 20 | 60 |

DESCRIPTION

Polyurethane based, one component, medium hardness general purpose construction and automotive sealant. **Properties:** Single component, easy to apply. Fast-cure. Resistant to weather conditions and UV radiation. Can be overpainted. Does not sag. Permanently elastic. Chemical resistance is high. Becomes waterproof when cured. Excellent adhesion to many building materials.

Application Areas: Indoor and outdoor. All kind of sealing and bonding applications in construction. Assembly and sealing of construction elements such as concrete, metal, wood, PVC, betopan. Assembly and isolation of sandwich panel in roof and facade. In manufacturing applications such as automotive, containers, trucks. Roof and terrace dilatations and in joints of parapet corners.



Automotive
Construction

*The minimum order quantity of Sibax products is 1000 pieces.

HYBRIDS HYBRID PRODUCT GROUP



Hybrid Stpu High-Tack Adhesive Sealant
Hybrid Stpu Crystal Adhesive Sealant
Hybrid Stpu Sealant

NS78 HYBRID HIGH-TACK ADHESIVE SEALANT

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|-----------------|-------|---------|--------------|
| 290 ml | White | 12 | 216 |
| 80 ml (Blister) | White | 36 | 120 |

DESCRIPTION

STPE based montage adhesive with extreme high-grab properties (320 kg/10 cm²) of final strength and initial tack.
Properties: Thanks to high-grap property enables to bond construction materials without mechanical fixing and initial support. Very strong adhesion on wood, glass, concrete, tile, brick, plaster, some plastics and metal. Absorbs vibrations due to its elasticity and therefore usable in moving building elements. Usable in damp substrates. Does not contain isocyanates, solvents and silicones. Applicable for interior and exterior applications for any weather conditions. Good workability.
Application Areas: Fixing baseboard, door fillers, window and door sills. Bonding polystyrene cornices and curtain tracks. Used for gluing sinks. Bonding metal, plastic and wooden building accessories. Installing heat and sound insulation boards. Bonding mirrors.



NS78U HYBRID ULTRA HIGH-TACK ADHESIVE SEALANT

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|-------|---------|--------------|
| 290 ml | White | 12 | 216 |

DESCRIPTION

STPE based montage adhesive with super extremely high-grab properties of final strength and initial tack in 5 seconds.
Properties: Thanks to high-grap property enables to bond construction materials without mechanical fixing and initial support. Very strong adhesion on wood, glass, concrete, tile, brick, plaster, some plastics and metal. Absorbs vibrations due to its elasticity and therefore usable in moving building elements. Usable in damp substrates. Does not contain any isocyanates, solvent and silicones. Applicable for interior and exterior applications for any weather conditions. Good workability.
Application Areas: Fixing baseboard, door fillers, window and door sills. Bonding polystyrene cornices and curtain tracks. Used for gluing sinks. Bonding metal, plastic and wooden building accessorie. Installing heat and sound insulation boards. Bonding mirrors



NS78UT HYBRID ULTRA TURBO HIGH-TACK ADHESIVE SEALANT

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|-------|---------|--------------|
| 290 ml | White | 12 | 216 |

DESCRIPTION

STPE based montage adhesive with very fast curing and super extremely high-grab properties of final strength and initial tack in 5 seconds. The final bonding strength properties competed rapidly in 6 hours.
Properties: Thanks to high-grap property enables to bond construction materials without mechanical fixing and initial support. Very strong adhesion on wood, glass, concrete, tile, brick, plaster, some plastics and metal. Absorbs vibrations due to its elasticity and therefore usable in moving building elements. Usable in damp substrates. Does not contain any isocyanates, solvent and silicones. Applicable for interior and exterior applications for any weather conditions. Good workability.
Application Areas: Fixing baseboard, door fillers, window and door sills. Bonding polystyrene cornices and curtain tracks. Used for gluing sinks. Bonding metal, plastic and wooden building accessories. Installing heat and sound insulation boards. Bonding mirrors.



*The minimum order quantity of Sibax products is 1000 pieces.



NS⁷⁹ HYBRID STPU CRYSTAL ADHESIVE SEALANT

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|-------------|---------|--------------|
| 290 ml | Transparent | 12 | 216 |

DESCRIPTION

Cristal clear adhesive and sealant produced with advanced MS polymer (STP) technology.
Properties: Extra transparent aesthetic appearance. Instant hold feature. It does not contain solvent and isocyanate. It always shows elasticity after full drying. Powerful and flexible. Can be used indoors and outdoors. Does not lose volume. Dries without air bubbles.
Application Areas: Can be used on many materials, including plastic, fiberglass, wood, glass, concrete, tiles and some plastics. In sealing applications around glass materials. In flexible bonding applications.



LS^{90S} HYBRID STPU SEALANT

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|-----------------------------------|---------|--------------|
| 290 ml | White, Grey, Black, *Other Colors | 12 | 216 |

DESCRIPTION

MS polymer based, single component, high modulus (HM) sealant and adhesive with hybrid strength and elasticity.
Properties: Single component, easy to apply. Resistant to weather conditions and UV radiation. Can be overpainted. Does not contain solvent and isocyanate, long life, does not lose volume and mass. Permanently elastic. Tolerates movements in the joints and protects its isolation and adhesion properties thanks to its high modulus. Excellent adhesion to many building materials.
Application Areas: Indoor and outdoor. All kind of sealing and bonding applications in construction. Assembly and sealing of construction elements such as concrete, metal, wood, PVC, betopan. Assembly and isolation of sandwich panel in roof and facade. In manufacturing applications such as automotive, containers, trucks. Roof and terrace dilatations and in joints of parapet corners. Intersections of the prefabricated elements. Filling joints of natural materials such as marble, natural stone, granite.



LS^{91S} HYBRID STPU SEALANT

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|-----------------------------------|---------|--------------|
| 600 ml | White, Grey, Black, *Other Colors | 20 | 60 |

DESCRIPTION

MS polymer based, single component, high modulus (HM) sealant and adhesive with hybrid strength and elasticity.
Properties: Single component, easy to apply. Resistant to weather conditions and UV radiation. Can be overpainted. Does not contain solvent and isocyanate, long life, does not lose volume and mass. Permanently elastic. Tolerates movements in the joints and protects its isolation and adhesion properties thanks to its high modulus. Excellent adhesion to many building materials.
Application Areas: Indoor and outdoor. All kind of sealing and bonding applications in construction. Assembly and sealing of construction elements such as concrete, metal, wood, PVC, betopan. Assembly and isolation of sandwich panel in roof and facade. In manufacturing applications such as automotive, containers, trucks. Roof and terrace dilatations and in joints of parapet corners. Intersections of the prefabricated elements. Filling joints of natural materials such as marble, natural stone, granite.



LS⁸⁰ HYBRID PARQUET ADHESIVE

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|-------|---------|--------------|
| 600 ml | - | 20 | 60 |
| 8 kg | - | - | 60 |
| 15 kg | - | - | 44 |

DESCRIPTION

Single component elastic parquet adhesive with MS functional polymer. Ready to use with its special solvent, isocyanate free formulation.
Properties: Easy to apply (spreads very easily whilst maintaining stable trowel peaks). Cost effective. Environment friendly (solvent & isocyanate free). Suitable for under-floor heating systems. Good workability, enough working time.
Application Areas: Suitable for bonding many different types of floors such as plank floors, mosaic parquet, concrete, wood, cement type subfloors and ceramic tiles.

SILICONIZED ACRYLIC SEALANTS

SILICONIZED & ACRYLIC SEALANT PRODUCT GROUP



Super Flexi Siliconized Sealant
 Performance Siliconized Sealant
 Fire Resistant Sealant
 Acrylic Sealant
 Siliconized Sealant

1001^{End} SUPER FLEXI SILICONIZED SEALANT

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|--|---------|--------------|
| 310 ml | White, Brown, Grey, Anthracite, Golden Oak | 24 | 100 |
| 400 ml | White, Brown, Grey, Anthracite, Golden Oak | 24 | 72 |
| 600 ml | White | 20 | 60 |

DESCRIPTION

Maximum performance, indoor and outdoor sealant with high and permanent elasticity.
Properties: High mobility. Strong adhesion. Weather resistant. Antibacterial. Can be painted over
Application Areas: In expansion joints between prefabricated building elements. In the assembly of wooden, pvc, iron, aluminum joinery. In plastering joint joints of all kinds of joinery. In movable construction joints.

501^{End} PERFORMANCE SILICONIZED SEALANT

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|----------------------|---------|--------------|
| 310 ml | White, *Other Colors | 24 | 100 |
| 400 ml | White, *Other Colors | 24 | 72 |

DESCRIPTION

Joint filling mastic with increased polymer ratio, improved sealing and elasticity.
Properties: Easy to apply. After drying, it forms a waterproof plastic elastic layer. Excellent adhesion to moist and absorbent surfaces. High movement capability. Strong adhesion. Suitable for outdoor applications. Antibacterial. Over paintable.
Application Areas: Expansion joints between prefabricated structural elements. Assembly of wooden, pvc, iron and aluminium panels as well as their plaster joints. Joints between aluminum roof elements. In the combinations of all kinds of joinery, plaster, marine and other building materials,

LS¹⁵ FIRE RESISTANT SEALANT

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|--------------------|---------|--------------|
| 310 ml | White, Black, Grey | 24 | 120 |
| 600 ml | White, Black, Grey | 20 | 60 |

DESCRIPTION

It is a high quality, single-component, water-based, fire-resistant acrylic building sealant.
Properties: Very easy to apply. Waterproof and colorless after curing. Can be painted after curing. It can be used on many porous surfaces.
Application Areas: In applications requiring fire resistance such as ovens, electrical parts, fire doors. Filling cracks and voids in concrete and plaster. It is used in connection joint applications in the construction industry

LS³³ SILICONIZED SEALANT (EN 15651-1) **CE**

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|---------------------------------------|---------|--------------|
| 500 gr | White, Brown, Grey, Black, Anthracite | 24 | 120 |

LS³⁴ SILICONIZED SEALANT (EN 15651-1) **CE**

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|---------------------|---------|--------------|
| 600 ml | White,*Other Colors | 20 | 60 |

DESCRIPTION

General purpose silicone sealant based on acrylic dispersion with increased mobility and adhesion strength.
Properties: Single component and water based; easy to apply and easy to clean. Good adhesion on porous substrates as concrete, brick, and wood.
Application Areas: Filling and sealing in gaps around door and window extrusions. Sealing in joints between construction materials. Filling cracks on walls and ceilings.

LS³⁵ SILICONIZED SEALANT (EN 15651-1) **CE**

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|---------------------------------------|---------|--------------|
| 400 ml | White, *Other Colors | 24 | 72 |
| 25 kg | White, Brown, Grey, Black, Anthracite | - | 27 |

DESCRIPTION

General purpose silicone sealant based on acrylic dispersion with increased mobility and adhesion strength.
Properties: Single component and water based; easy to apply and easy to clean. Good adhesion on porous substrates as concrete, brick, and wood. Maintains its elasticity after full cure, does not crack. Resistant to weather conditions. Over-paintable and odourless.
Application Areas: Filling and sealing in gaps around door and window extrusions. Sealing in joints between construction materials. Filling cracks on walls and ceilings.

LS⁴⁴ ACRYLIC SEALANT (EN 15651-1) **CE**

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|----------------------|---------|--------------|
| 475 gr | White, *Other Colors | 24 | 120 |

LS²⁴ ACRYLIC SEALANT (EN 15651-1) **CE**

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|----------------------|---------|--------------|
| 450 gr | White, *Other Colors | 24 | 120 |

DESCRIPTION

Acrylic dispersion based, general purpose sealing and filling material.
Properties: Single component, easy to apply. After hardening, it is not affected by weather conditions. Paintable. Odourless. Can be used in many porous surfaces.
Application Areas: Indoor and outdoor. Expansion joints between prefabricate construction materials. Installation of wooden, pvc, iron, aluminium joinery. Joints of all kinds of building materials.

LS⁴⁶ SILICONIZED SEALANT (EN 15651-1) **CE**

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|----------------------|---------|--------------|
| 450 gr | White, *Other Colors | 24 | 120 |

DESCRIPTION

Siliconeized general purpose sealant with acrylic dispersion with increased mobility and adhesion strength.
Properties: Single component, easy to apply. After hardening, it is not affected by weather conditions. Paintable. Odourless. Can be used in many porous surfaces.
Application Areas: Indoor and outdoor. Expansion joints between prefabricate construction materials. Installation of wooden, pvc, iron, aluminium joinery. Joints of all kinds of building materials. As an insulation material for cracks on walls. Sealing of window and door frames

LS⁵⁰ CLEAR SILICONIZED SEALANT

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|-------------|---------|--------------|
| 280 ml | Transparent | 24 | 120 |

DESCRIPTION

Highly elastic, easy-to-use water-based acrylic sealant that becomes transparent when dry.
Properties: Suitable for glass, concrete, gypsum, metal, fiberglass, wood and polycarbonate and some plastics. %25 movement capability. Contains fungicides against mould. Easy to use, water clean up. Odorless. Can be used indoors and outdoors. Becomes clear while curing. Neutral cure, does not cause corrosion. Over paintable.
Application Areas: Expansion joints between prefabricated structural elements. Assembly of wooden, pvc, iron and aluminium panels as well as their plaster joints. Joints between aluminum roof elements.

*The minimum order quantity of Sibax products is 1000 pieces.

*The minimum order quantity of Sibax products is 1000 pieces.

ADHESIVES

ADHESIVE PRODUCT GROUP



- Pu Marine Express Wood Adhesive - Transparent
- Pu Marine Wood Adhesive - Amber
- Acrylic Water Based Assembly Adhesive - Liquid Nail
- Pu Express Assembly Adhesive - Liquid Nail
- Chemical Anchor
- Fast Adhesive Mdf-Kit
- Super Glue

NS³³ PU MARINE EXPRESS WOOD ADHESIVE - TRANSPARENT

| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 500 gr | 24 | 36 |

DESCRIPTION

Polyurethane based fast-cure and low-viscosity liquid transparent adhesive.

Properties: Transparent, light yellow. Short open-time and pres-time. Flowable and low viscosity. Gap filling property with limited expansion. Extremely resistant to water, moisture and weather conditions. It has strong adhesion to many building materials such as wood, concrete, metal, polyurethane and polystyrene foam, natural stone, mdf, ceramic glass and PVC. Odorless.

Application Areas: Bonding almost every type of wood to each other; to metals; to stone, bricks and concrete. Bonding and repairing wooden construction materials. Furniture production and mending.



NS⁴⁴ PU MARINE WOOD ADHESIVE - AMBER

| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 500 gr | 24 | 36 |

DESCRIPTION

Polyurethane based, water-proof, liquid adhesive with gap filling properties.

Properties: Do not connect wood to each other and to concrete, metal and some plastics bonds strongly. Can be used indoors and outdoors. It makes limited growth, fills the gaps. It is highly resistant to water, humidity and weather conditions. It is in D4 class (According to DIN -EN 204 standard). It can be painted over. Solvent free, odorless.

Application Areas: Almost all kinds of wood together; to metal; to some plastics; stone, bonding to brick and concrete. For bonding and repairing wooden construction elements. In furniture production and repair.



NS⁵⁸ ACRYLIC WATER BASED ASSEMBLY ADHESIVE - LIQUID NAIL - WHITE

| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 280 ml | 12 | 216 |

DESCRIPTION

Acrylic dispersion-based assembly adhesive with high initial tack strength for lightweight construction elements. **Properties:** Ability to fill gaps. Suitable for uneven surfaces. Particularly suitable for interior applications. Solvent-free. Easy to apply and clean. Correctable.

Application Areas: Bonding many kinds of building materials such as wood, stone, concrete, metal, many synthetics and polystyrene foam onto porous surfaces of stone, concrete, wood, plaster, drywall, etc.



NS⁶⁸ PU EXPRESS ASSEMBLY ADHESIVE - LIQUID NAIL (D4) - TRANSPARENT

| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 280 ml | 12 | 216 |

DESCRIPTION

Very rapid curing, water and humidity resistant, translucent wood adhesive in gel consistency.

Properties: Very rapid cure; short open-time and minimum clamping-time. Becomes tack-free within ten minutes; maximum strength in

up to 12 hours. Gap filling property. Resistant to humidity, water and sea water; meets D4. Bonds almost every sort of wood to each other and to metal, tile, glass and stone. Translucent appearance. Non-sag gel consistency.

Application Areas: Wooden furniture production. Boat and yacht production. Wooden door and window production and assembly. Bonding metal, glass, tile and stone elements on wood.





NS⁶⁹ PU LIQUID NAIL - BEIGE / GREY

| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 310 ml | 12 | 216 |

DESCRIPTION

Very rapid curing, water and humidity resistant, wood adhesive in gel consistency.
Properties: Very rapid cure; short open-time and minimum clamping-time. Becomes tack-free within ten minutes; maximum strength in up to 12 hours. Gap filling property. Resistant to humidity, water and sea water; meets D4. Bonds almost every sort of wood to each other and to metal, tile, glass and stone. Non-sag gel consistency.
Application Areas: Wooden furniture production. Boat and yacht production. Wooden door and window production and assembly. Bonding metal, glass, tile and stone elements on wood.

BS^{09/08/07} CHEMICAL ANCHOR

| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------------------|---------|--------------|
| BS ⁰⁹ / 300 ml | 20 | 75 |
| BS ⁰⁸ / 345 ml | 20 | 64 |
| BS ⁰⁷ / 410 ml | 20 | 60 |

DESCRIPTION

Polyester-based adhesive that provides heavy load resistance in all construction materials.
Properties: Use for medium-high loads, static or quasi-static. Working life of 50 and/or 100 years. Dry, wet and flooded holes. Temperature range: from -40°C to +80°C (long term maximum temperature +50°C). Compatible with several building materials including perforated brick.
Application Areas: Masonry support. Handrails, Fences. Balcony parapets. Road signs. Pipe systems. Lighting systems. Canopies. Safety barriers. Racking, machinery. Ventilation systems.

BS^{12/14} FAST ADHESIVE MDF-KIT

| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|------------------------------------|---------|--------------|
| BS ¹² / 200 ml / 50 gr | 24 | 99 |
| BS ¹⁴ / 400 ml / 100 gr | 24 | 54 |

DESCRIPTION

High viscosity, extremely fast curing cyanoacrylate adhesive with an aerosol activator.
Properties: Two-component adhesive with non-slump cyanoacrylate and solvent-based activator. Enables a very strong bond within 5 seconds. Can be used on vertical and porous substrates.
Application Areas: MDF. Rubber. Leather. Some plastics. Bonding wood elements. DIY bonding where fast adhesion is desired.

BS^{12C/14C} SUPER GLUE

| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|----------------------------|---------|--------------|
| BS ^{12C} / 50 gr | 50 | 40 |
| BS ^{14C} / 100 gr | 50 | 40 |

DESCRIPTION

Low viscosity gel type cyanoacrylate adhesive, convenient to use for vertical applications.



SPRAY PAINTS

**10 YEARS
SHELF LIFE**



ACRYLIC SPRAY PAINT



| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|--------------------|---------|--------------|
| 400 ml | Solid Colors | 12 | 160 |
| 400 ml | Metallic Colors | 12 | 160 |
| 400 ml | Fluorescent Colors | 12 | 160 |
| 400 ml | Efect Colors | 12 | 160 |
| 250 ml | Solid Colors | 30 | 96 |

| WEIGHT/VOLUME | COLOR | QTY/BOX | BOXES/PALLET |
|---------------|-----------------------------|---------|--------------|
| 400 ml | Solid Colors (Gross 300 gr) | 12 | 160 |

DESCRIPTION

Acrylic-based, solvent-borne, high-gloss top-coat paint with good covering and quick drying abilities.
Properties: Formulated with acrylic film forming agent and non-toxic solvents. Good coverage and filling properties. Lasting colour and gloss. Excellent adhesion.
Application Areas: Ideal for use on wood. Metal. Glass. Ceramic materials. Various plastics. Hobby. Decoration. Automotive. Industry etc. it can be used for retouching and general repair in areas.

PRE-FILLED SPRAY CAN



| WEIGHT/VOLUME | COLOR | BOXES/PALLET |
|---------------|-------|--------------|
| 400 ml | 24 | 80 |

DESCRIPTION

Properties: Featuring innovative spray and aerosol valve technology. Thanks to the feature of the aerosol valve system, a spray similar to the result of the spray gun is obtained. Best workmanship and professional quality results. Guarantees high application rate and constant pressure. Simple, time-saving application. The propellant contains specific solvent materials.
Application Areas: For professional use. Ideal for stain repairs or repair parts. It is used in vehicles, work machines, white goods. All kinds of metal and wooden surfaces and for hobby purposes.

Rapid Seal SEALING SPRAY



| WEIGHT/VOLUME | COLOR | BOXES/PALLET |
|---------------|-------|--------------|
| 400 ml | 24 | 80 |

DESCRIPTION

It is a protective waterproofing material that can be used to fill and seal leaks, cracks.
Properties: It can be painted over. It has high resistance to abrasion. Dries fast. Suitable for all commonly used surfaces. It is resistant to aging. It has high elasticity. The adhesion strength is high.
Application Areas: For waterproofing on hard-to-reach surfaces of buildings. For the repair of cracks in Pimas pipes.

HEAT RESISTANT COLORS

| WEIGHT/VOLUME | COLOR | BOXES/PALLET |
|---------------|-------|--------------|
| 400 ml | 12 | 160 |

DESCRIPTION

High temperature resistant solvent based silicone aerosol paint.
Properties: Resistant to high temperatures. Excellent adhesion ability. Solvent based silicone aerosol paint. Ideal for surfaces exposed to temperatures of 300°C-650°C. For painting surrounding parts in areas exposed to heat. It is an ideal spray paint for iron and steel industry and auto body repairers.
Application Areas: It is applied on surfaces that may be exposed to high temperatures such as stoves and fireplaces. There is no need for primer. It can be easily applied to all metal surfaces.

TEMPORARY MARKING PAINT

| WEIGHT/VOLUME | COLOR | BOXES/PALLET |
|---------------|-------|--------------|
| 400 ml | 12 | 160 |

DESCRIPTION

Fast drying, high covering solvent based temporary marking paint.
Properties: Can be easily cleaned with water. Fast drying: approximately 10 minutes Marking time is minimum 1 day and maximum 1 month.
Application Areas: Ideal for use on concrete, wood, grass and asphalt surfaces.

SOLID COLORS

- 9010 Gloss White
- 6002 Leaf Green
- 9010 Matte White
- 6005 Moss Green
- 9016 Traffic White
- 6016 Turquoise Green
- 301 White
- 6018 Yellow Green
- 1013 Oyster White
- 7001 Silver Grey
- 1015 Ivory
- 7015 Slate Grey
- 1023 Traffic Yellow
- 7016 Anthracite Grey
- 1018 Zinc Yellow
- 7016 Matte Anthracite Grey
- 1003 Signal Yellow
- 7035 Light Grey
- 2002 Vermillion
- 7040 Window Grey
- 2004 Orange
- 8003 Clay Brown
- 3002 Carmine Red
- 7032 Pebble Gray
- 3000 Flame Red
- 8016 Mahogany Brown
- 3020 Traffic Red
- 3005 Vine Red
- 4003 Heather Violet
- 9005 Matte Black
- 4005 Blue Lilac
- 9005 Gloss Black
- 5002 Ultramarine Blue
- 9006 M. Aluminium Grey
- 5010 Gention Blue
- 9005 Semi-Matte Black
- 5012 Light Blue
- 3009 Oxide Red
- 5015 Sky Blue
- 7046 Telegrey
- 5017 Traffic Blue
- 6001 Emerald Green
- 5018 Turquoise Blue
- Matte / Gloss Varnish

FLUORESCENT COLORS

- Fluorescent Yellow
- Fluorescent Red
- Fluorescent Dark Red
- Fluorescent Orange
- Fluorescent Green
- Fluorescent Blue

EFFECT COLORS

- Gold Effect
- Aluminium Effect
- Silver Effect
- Inox Effect
- Chrome Effect
- Zinc Effect

HEAT RESISTANT COLORS

- Heat Resistant Aluminium
- Heat Resistant Black
- Heat Resistant White
- Heat Resistant Red

METALLIC COLORS

- Metallic Blue
- Metallic Grey
- Metallic Black
- Metallic Rim Silver

*These colors may differ from original colors. Please ask us for detailed information.

250 ml and 300 gr spray paint colors.

INDUSTRIAL SPRAYS



SB¹⁰⁰⁰ BRAKE & PARTS CLEANER

| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 500 ml | 24 | 80 |

E-100 ENERGIE BRAKE & PARTS CLEANER

| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|-----------------------|---------|--------------|
| 500 ml (Gross 350 gr) | 24 | 80 |

DESCRIPTION

Used to clean breaks, brake pads, drums, gearbox and differential gear parts. Easily removes hydraulic brake fluids, grease and oil, increase the performance and prevent squeaks thanks to its special formulation.

Properties: Volatile, leaving no residuals on the surface. Improves brake performance. Prevents squeaks. Increases the properties of parts. 180° can also be used upside down.

Application Areas: It is used to clean the calliper and pads. Discs. Drums. Brake master cylinder. Vices. Springs and clutch parts in the brake system and to increase the holding feature.

SB²⁰⁰⁰ PENETRATING OIL MoS²

| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 200 ml | 36 | 90 |
| 400 ml | 24 | 80 |

DESCRIPTION

Prevents rust, loosens stuck parts.

Properties: Prevents corrosion and rust that may occur on surfaces exposed to rust and moisture. Reduces friction and wear. It can be used safely in many industrial areas, as well as on all corroded surfaces at home and workplaces. Thanks to the oily surface it leaves behind, it extends the maintenance intervals and provides cost savings with spare parts savings, After removing the rust, it forms a thin film layer on the surface and delays the rusting in the later stages. It is water repellent. Does not damage rubber and gaskets. Does not contain silicone. 360 degrees can be applied.

Application Areas: It is used on all surfaces where corrosion and rusting is observed at home and in the workplace.

SB³⁰⁰⁰ LIQUID GREASE & LUBRICATING SPRAY

| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 500 ml | 24 | 80 |

DESCRIPTION

Prevents friction and corrosion.

Properties: It is a multi-purpose lubricating spray. It is lubricant. Reduces friction and corrosion. Delays or prevents malfunctions by increasing the frictional strength of moving parts it helps. Thanks to the oily surface it leaves behind, it provides cost saving by extending maintenance intervals. It does not contain silicone. 360 degrees can be applied.

Application Areas: All kinds of mechanical systems are used in hinges, chain and gear systems, beds, machines, forklifts, gear wheels, motorcycle and bicycle chains.

SB³¹⁰⁰ CHAIN LUBE SPRAY

| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 400 ml | 24 | 80 |

DESCRIPTION

A spray lubricant that adheres to moving parts, maximizing lubrication performance while significantly reducing friction and wear.

Properties: Suitable for dry, wet, or variable conditions. Prevents squeaking while reducing wear. Non-drying formulation extends chain life. Corrosion-inhibiting. Provides resistance to high temperatures. Leaves no residue and does not damage metals or alloys. Enables fast and easy cleaning.

Application Areas: Suitable for use in many applications such as bicycle, motorcycle, and industrial chains.



INDUSTRIAL SPRAYS





SB³²⁰⁰ DRY LUBE SPRAY

| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 400 ml | 24 | 80 |

DESCRIPTION

A PTFE-based lubricant spray that forms a thin, dry film without containing silicone, resin, or mineral oil. With its dry lubrication property, it provides effective cleanliness against dirt, dust, and oil at friction points.
Properties: Provides a clean, dry, and oil-free appearance. Prevents corrosion and moisture formation. Dries quickly. Resistant to high temperatures (≈260 °C). Spray film is resistant to water, mild acids, and salt water; offers high chemical stability. Minimizes “stick-slip” problems. Extends the service life of machinery and equipment.
Application Areas: Metal machine components. Leather, plastics, and many elastomers. Various everyday applications such as door locks, furniture and cabinet drawer slides, zippers. Musical instruments, camera and film shutters. Paper, fabric, and textile applications.

SB⁴⁰⁰⁰ MULTI SPRAY

| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|----------------------------|---------|--------------|
| 200 ml (Standard Actuator) | 36 | 90 |
| 400 ml (Standard Actuator) | 24 | 80 |
| 400 ml (Cobra Actuator) | 24 | 80 |

DESCRIPTION

High quality, multi-purpose spray.
Properties: Cleans. Lubricant. Preserves. It silences the squeaks. It operates rusted mechanisms. It removes moisture. It is used in places where water and moisture are undesirable. Protects against corrosion. It is suitable for indoor and outdoor use. The aerosol can be applied with a 360° angle. Cooling and shrinkage effect (shock spray).
Application Areas: Used as multi-purpose lubricant. It can be used as a multi-purpose lubricant in machinery, roller bearings, axles, gear wheels, conveyor belts, rubber seal profiles. It is resistant to corrosion. It remains on the surface as a protective film. It is used for cleaning purposes. It does not damage rubber, plastics or metals.

SB⁵⁰⁰⁰ UNDERBODY SPRAY (ANTI - GRAVILLION PAINT)

| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 400 ml | 24 | 80 |
| 1000 ml | 12 | 64 |

DESCRIPTION

It is a resin-based, strong, durable, and protective rough coating.
Properties: It creates a protective film against stone impacts and corrosion in the underfloor sections of vehicles. Provides good sound insulation. It can be painted again.
Application Areas: Interior walls. Exterior wall painting. Wooden surfaces. Iron and metal surfaces. Drywall and gypsum surfaces. Vehicle starter. Vehicle fender interiors.

SB⁶⁰⁰⁰ MOLD RELEASE SPRAY - SILICONE

| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 400 ml | 24 | 70 |

DESCRIPTION

With silicone containing formula, it provides effective separation of rubber parts from the moulds.
Properties: Ensures that molds come out smoothly and do not get damaged. Reduces friction in molds and prevents sticking. Speeds up production in the mold separation process. Can be used in low and high temperature ranges.
Application Areas: Used in all types of mold separation processes such as metal, rubber, silicone, plastic, etc. It is not used in processes that will be painted later.

SB⁶⁰⁰⁰ MOLD RELEASE SPRAY - SILICONE - FREE

| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 400 ml | 24 | 70 |

DESCRIPTION

Special silicone-free formula ensures that rubber parts are effectively separated from the moulds.
Properties: It can be applied to all mold surfaces. It ensures that molds come out smoothly and are not damaged. It reduces friction in molds and prevents sticking. It speeds up production in mold separation process. It can be used in low and high temperature ranges.
Application Areas: It is used in all kinds of mold separation processes such as metal, rubber, silicone, plastic, etc.

SB⁷⁰⁰⁰ WELDING SPRAY - SILICONE

| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 400 ml | 24 | 80 |

DESCRIPTION

Spray that prevents burrs formed during welding from sticking to the nozzle and workpart thanks to its special formula containing silicone.
Properties: Creates a protective layer that prevents sticking. Extends the nozzle life of tools and welding units. Since splashes do not stick to the surface, they can be easily wiped o.
Application Areas: It is used without any problems in all gas metal arc welding performed in wide temperature ranges. It should not be used on surfaces that will be painted after welding.

SB⁷⁰⁰⁰ WELDING SPRAY - SILICONE - FREE

| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 400 ml | 24 | 80 |

DESCRIPTION

Environmentally friendly spray that prevents the burrs formed during the welding process from sticking to the nozzle and workpart.
Properties: Creates a protective layer that prevents sticking. Extends the nozzle life of tools and welding units. Since splashes do not stick to the surface, they can be easily wiped o.
Application Areas: It is used without any problems in all gas metal arc welding performed in wide temperature ranges.

SB⁸⁰⁰⁰ PAINT REMOVER

| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 400 ml | 24 | 80 |

DESCRIPTION

Thanks to its solvent-based and surface tension increasing chemical composition, it adheres to the surface and enables paints to be easily removed from the surface.
Properties: It allows easy removal of old paint on surfaces that need to be cleaned of paint or where color change will be made before the change. It does not damage the surface and prevents damage that may be caused by hard scraping processes. It provides an even and easy distribution to the application area.
Application Areas: It is used in many cleaning processes such as cleaning dry and baked paints, polyurethanes, varnishes, sealants, adhesive and tape residues from the surface.





SB8100 LABEL REMOVER SPRAY

| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 200 ml | 36 | 90 |

DESCRIPTION

A spray designed to remove adhesive residues, tapes, and labels from various surfaces.
Properties: Cleans surfaces effectively without leaving residue or requiring physical scrubbing. Leaves no stains or marks. Suitable for use on painted surfaces. Non-abrasive.
Application Areas: Can be used on a wide range of surfaces such as metal, glass, ceramic, porcelain, plastic, and enamel. Suitable for use on vehicle areas like windows, bumpers, and bodywork.



SB8200 SEALANT REMOVER SPRAY

| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 400 ml | 24 | 80 |

DESCRIPTION

A spray designed to easily remove cured silicone, adhesive, and resin residues from surfaces. It allows easy removal of old silicone in areas such as bathrooms and kitchens, speeding up cleaning operations. Effectively removes oil, carbon residues, paint, and varnish, and eliminates oil, resin, grease, and tar.
Properties: Easily removes hardened silicone and similar sealing materials. Effective even on vertical surfaces. Efficiently cleans oil, carbon residues, paint, and resins. Safe and practical to use.
Application Areas: Countertop joints. Tile and marble surfaces. Suitable for use on many different surfaces such as glass, metal, and wood.



SB9000 TIRE REPAIR KIT

| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 400 ml | 24 | 80 |

DESCRIPTION

It is a product that can be used to instantly inflate and repair punctured tires.
Properties: Allows you to inflate and repair the tire without removing it. Allows you to continue for kilometers without repairing the tire. Easy and fast to apply. Does not damage the structure of the tire and rim with its special formula.
Application Areas: Suitable for use on all passenger cars, motorcycles, bicycles and light commercial vehicles. Not used on excessive tears.



SB9100 TYRE SHINE SPRAY

| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 500 ml | 24 | 80 |

DESCRIPTION

A spray cleaner suitable for all vehicle tires that removes dirt, dust, and oil.
Properties: Restores the natural black appearance of tires with a wet and glossy finish. Thanks to its antistatic formula, it delays dust formation for a long time. It can be used from daily use to detailed routine cleaning. Thanks to its special non-corrosive formula, it does not damage the rims.
Application Areas: Can be used in all conditions from daily maintenance to detailed cleaning routines.

SB9200 WATERLESS ENGINE CLEANER SPRAY

| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 500 ml | 24 | 80 |

DESCRIPTION

A waterless spray with a non-foaming special formula that cleans all types of oil, dust, and stubborn dirt on engines.
Properties: Easily reaches and penetrates hard-to-access areas within engine components. Leaves no residue on the surface and, thanks to its insulating formula, does not harm electrical components. It delays dust formation for a long time thanks to its antistatic feature. Does not cause corrosion or abrasion. Provides a shiny finish.
Application Areas: Suitable for all types of engines, including passenger vehicles, motorcycles, lawnmowers, and similar equipment.



SB9300 COCKPIT SHINER SPRAY

| WEIGHT/VOLUME | FRAGRANCE OPTIONS | QTY/BOX | BOXES/PALLET |
|---------------|---|---------|--------------|
| 220 ml | Anti-Tobacco, Strawberry, Dark Angel, Exotic, Melon, Lavender, Lemon, Mango, Ocean Breeze, New Car Fragrance, Vanilla | 12 | - |

DESCRIPTION

A spray that effectively cleans and shines leather and plastic surfaces on the vehicle's dashboard and other interior components.
Properties: Prolongs the life of upholstery and surfaces with regular use. Leaves a pleasant fragrance inside the vehicle thanks to its scented formula. Antistatic properties delay dust buildup for an extended period. Provides a glossy finish.
Application Areas: Suitable for dashboards, leather, and plastic surfaces inside the vehicle.



SB9400 AIR CONDITIONER CLEANER & DEODORIZER SPRAY

| WEIGHT/VOLUME | FRAGRANCE OPTIONS | QTY/BOX | BOXES/PALLET |
|---------------|--|---------|--------------|
| 200 ml | Dark Angel, Lemon, Ocean Breeze, New Car Fragrance | 12 | - |

DESCRIPTION

A spray with an anti-allergic formula that eliminates bacteria in vehicle interiors and air vents, removing unpleasant odors.
Properties: Leaves a long-lasting fresh and clean scent. Enhances driving comfort after application. No additional devices or tools are needed for use. Can be used without removing the pollen or dust filter.
Application Areas: Used in vehicle air conditioning systems.



SB9500 UPHOLSTERY CLEANER SPRAY

| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 400 ml | 24 | 80 |

DESCRIPTION

A spray that effectively cleans and shines leather and plastic surfaces on the vehicle's dashboard and other interior components.
Properties: Penetrates into fabric surfaces to eliminate embedded dirt. Does not damage the fabric texture. Leaves no residue and revitalizes fabric colors. Easy and fast application thanks to spray form. Neutralizes unpleasant odors such as cigarette smoke and pet smells, leaving a pleasant fragrance. Does not require rinsing after application.
Application Areas: Sofas, chairs, carpets. Vehicle headliners, upholstery, door panels, and front dashboards.



PIRÜ PAK

PRO
CARE

A new era in cleaning: **Sibax Pirü Pak**

From kitchen to bathroom, from outdoor area to everyday surfaces,
it delivers effective solutions across countless applications.

With its powerful, surface-friendly formula, it sets a new standard in cleaning.



SB⁹⁷⁰⁰ PIRUPAK MULTI-PURPOSE CLEANING PASTE



| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 500 gr | 12 | 96 |

SB⁹⁸⁰⁰ PIRUPAK CLEANING SPRAY



| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 500 ml | 12 | 76 |

DESCRIPTION

A natural cleaning spray developed to easily dissolve stubborn dirt on surfaces with its concentrated and effective formula, free from harsh chemicals. It penetrates into surface dirt and eliminates it effectively.

Properties: Provides deep cleaning. Easy and fast application thanks to spray form. Leaves a pleasant fragrance during application. Does not require rinsing after application and provides surface shine. Offers excellent cleaning regardless of indoor or outdoor use.

Application Areas: Cooktops, ovens, extractor hoods, barbecues, pans, and trays. Sinks, showers, bathtubs, window and door surfaces. Outdoor furniture and ceramic surfaces. Tiles and grout. Automobile and bicycle rims.

NEW PRODUCT

Meet SB 112

Instant
Response

for Your Safety!



Environment safe

Harmless to skin

Easy to use

Prevents or delays the spread of fire

Not applicable to electrical installations



SB 112 FIRE EXTINGUISHER SPRAY

| WEIGHT/VOLUME | QTY/BOX | BOXES/PALLET |
|---------------|---------|--------------|
| 600 ml | 24 | 80 |
| 1000 ml | 16 | 96 |

DESCRIPTION

Fire extinguisher spray with a special formula developed for a much faster and more effective response at the beginning of fires.

Properties: It suffocates the fire by cutting off its contact with oxygen. Stops or delays the spread of fire. Easy to use thanks to its size. Harmless to skin.

Application Areas: It can be used in different areas such as home, office, tent, workshop, car, bus, motorcycle, caravan, boat. Not suitable for electrical fires.

NOTES

Lined area for notes on page 40, consisting of 25 horizontal dashed lines.

NOTES

Lined area for notes on page 41, consisting of 25 horizontal dashed lines.

SİBA

KİMYA VE ENDÜSTRİYEL ÜRÜNLER SAN. TİC. A.Ş.

Esentepe Mah. Milangaz Cad. No:75/A Kat:8
Monumento Plaza 34870 Kartal / İSTANBUL
Tel.: +90 216 504 58 58 Fax: +90 216 504 58 59



www.sibakimya.com.tr



SİBA IS A MEMBER OF LIDARS GROUP.