



ACHIEVE A FASTENER-FREE DECK SURFACE



HIDDEN FASTENING MADE EASY

The MARKSMAN tools and CAMO Edge Screws secure the board through the edge.

SOLUTIONS FOR EVERY BOARD

There's a tool and fastener combination for every square deck board.

THE BEST SCREW YOU'LL NEVER SEE

Edge Screws feature a patented rake tip that augers material as it's driven, reducing the potential for splitting and the need for pre-drilling*.

*Pre-drilling is required in capped composites and hardwood decking given the density of those boards.

All CAMO tools and screws are backed by a CAMO Warranty for use with leading deck boards. Read the full warranty at camofasteners.com



EDGE
SCREW



T-15 DRIVER BIT
FOR SQUARE
BOARDS



T-15 DRIVER BIT
FOR GROOVED
BOARDS



PRE-DRILL
BIT

HOW TO



SET YOUR TOOL ON THE BOARD. THE TEETH AUTOMATICALLY SPACE THE BOARDS.



PLACE AN EDGE SCREW IN EACH CHANNEL.



FASTEN USING THE INCLUDED DRIVER BIT.

INSTALLING HARDWOOD OR CAPPED COMPOSITE?

Run a pre-drill bit through the MARKSMAN tool screw channels before fastening with Edge screws.



**Using the MARKSMAN Edge?
Just load one screw and fasten.**



MARKSMAN PRO®

- Composite, PVC, cedar, redwood, hardwood, and KDAT
- Fits 5-1/4 in. (133mm) to 5-3/4 in. (146mm) boards
- Creates 3/16 in. (4.7mm) spacing



MARKSMAN PRO®-X1

- Pressure Treated
- Fits 5-1/4 in. (133mm) to 5-3/4 in. (146mm) boards
- Creates 1/16 in. (1.59mm) spacing



MARKSMAN PRO®-NB

- Narrow composite, PVC, cedar, redwood, hardwood, and KDAT
- Fits 3-1/4 in. (83mm) to 5 in. (127mm) boards
- Creates 3/16 in. (4.7mm) spacing



MARKSMAN EDGE

- Pressure Treated
- Single-shot no-gap tool



EDGE SCREWS ARE AVAILABLE IN:

- ProTech and 316 Stainless Steel. Use Stainless Steel for cedar, redwood, and hardwood installs.
- 1-7/8 in. (48mm) for boards 3/4-1 in. (19-25.4mm) thick and 2-3/8 in. (60mm) lengths for boards 1-1/2 in. (25.4-38.1mm) thick.
- 100 ct. (30 sq. ft., 2.79m²), 350 ct. (100 sq. ft., 9.29m²), 700 ct. (200 sq. ft., 18.58m²), and 1750 ct. (500 sq. ft., 46.5m²) pails.