# **Preassembled**

# Drain Pump Series Remove water from areas with no gravity flow.

This kit works great for laundry trays, wet bar sinks, lavatories, air conditioning condensate, and dehumidifiers. Can also be used in conjunction with dishwashers and garbage disposals. The included 1/3 HP submersible sump pump will move up to 43 gallons of water per minute and passes 1/2" solids.

## Features:

- Preassembled kit ready for installation
- Automatic Model 53® featuring inline check valve
- Built-in check valve simplifies installation
- Corrosion-resistant polypropylene basin with tank cord seals and basin cover
- No inlet filters or screens to clean
- Low profile, can be installed in base cabinet under a sink
- Trap can be installed inside basin

100% factory tested



Model 105-0017 shown



Trusted. Tested. Tough.


zoellerpumps.com 3649 Cane Run Road, Louisville, KY 40211 USA



FM3241 0420 Supersedes New

#### **TOTAL DYNAMIC HEAD FLOW PER MINUTE**

MODELS		105			
Feet	Meters	Gal.	Liters		
5	1.5	43	163		
10	3.0	34	129		
15	4.6	19	72		
Shut-off Head:		19.25 ft. (5.9m)			




Model	MODEL COMPARISON									
	Seal	Mode	Volts	Ph	Amps	HP	Hz	Lbs	Kg	
105	Single	Auto	115	1	9.7	1/3	60	30	14	

**AUTION** All installation of controls, protection devices and wiring should be done by a qualified licensed electrician. All electrical and safety codes should be followed including the most recent National Electrical Code (NEC) and the Occupational Safety and Health Act (OSHA).


#### **INTERNAL TRAP \*\***

#### Lavatory Sink




### **STANDARD INSTALL**


Laundry Tray Pump



Wet Bar With Sink



Dehumidifier or Air Conditioner



SK3281

Applications include: laundry tray pump, wet bar sink, lavatory, air conditioning condensate or dehumidifier water removal. It can also be used in conjunction with dishwashers and garbage disposal applications.