

**LMF**

**8.9**  
R-value  
ENERGY SAVING

**2**  
YEARS  
WARRANTY

**350**  
lbs  
LOAD CAPACITY

**60**  
min  
ASTM E119/ NFPA 288



**FIRE-RATED**

**LWF**

**9.5**  
R-value  
ENERGY SAVING

**2**  
YEARS  
WARRANTY

**300**  
lbs  
LOAD CAPACITY

**43**  
min  
ASTM E119

**30**  
min  
NFPA 288



**LMF**

- Certified fire-rated door
- 60 min. rated by ASTM E119
- 60 min. rated by NFPA 288
- Available for installation in high ceilings
- Sealed and insulated – R-value 8.9
- 3 weather seal gaskets stop air leaks
- 350 lbs load capacity

**LWF**

- Certified fire-rated door
- 43 min. rated by ASTM E119
- 30 min. rated by NFPA 288
- 3 inch thick insulated door
- Sealed and insulated – R-value 9.5
- 3 weather seal gaskets stop air leaks
- 300 lbs load capacity

**ATTIC LADDERS**



# LUX


**LST** INSULATED

22½ x 31½  
27½ x 31½  
22½ x 47  
25 x 47  
22½ x 54  
25 x 54  
30½ x 54

7'6½" - 9'2¼"

\*max. 10'10" with two extra LSS steps

5.2 R-value  




# PREMIUM


**LMP** INSULATED

22½ x 56½  
25 x 56½  
30 x 56½

9'10" - 12'

12'

5.2 R-value 



# BASIC

**LMB** INSULATED

22½ x 54  
25 x 54  
30 x 54

7'8" - 10'3"

3.7 R-value 





**LWT Thermo** Thermo


22½ x 47  
25 x 47

7'5" - 8'11"

22½ x 54  
25 x 54  
30 x 54

7'8" - 10'1"

12.5 R-value  



**LWP** INSULATED

22½ x 47  
25 x 47



7'5" - 8'11"


22½ x 54  
25 x 54  
30 x 54

7'11" - 10'1"

22½ x 54  
25 x 54  
30 x 54

8'8½" - 10'8"

5.9 R-value  



**LWB** INSULATED

22½ x 54  
25 x 54  
30 x 54

7'10" - 10'1"

3.7 R-value 





**LMF FIRE-RATED** INSULATED


22½ x 54  
25 x 54  
30 x 54

8'1" - 10'1"

25 x 56½  
30 x 56½

9'7½" - 11'10"

8.9 R-value  



**LSF FIRE-RATED** INSULATED

22½ x 47  
25 x 47

8'10¼" - 9'10⅞"

\*max. 10'6" with one extra LSS step

9.5 R-value   






**LWF FIRE-RATED** INSULATED


22½ x 47  
25 x 47

7'5" - 8'11"

22½ x 54  
25 x 54  
30 x 54

7'11½" - 10'1"

9.5 R-value   



**LML** INSULATED


23½ x 47  
27½ x 47


7'7¼" - 9'2¼"

27½ x 51

8'4¾" - 10'3"\*

\*max. 10'3" with stile ends

5.2 R-value 




**LMS** INSULATED


22½ x 47  
25 x 47

7'2" - 8'11"

22 x 54  
25 x 54  
30 x 54

7'11" - 10'1"

5.2 R-value  



## ACCESSORIES

Attic balustrade **LXB-U**



LXB-U

Insulated upper hatch **LXW-B**



LXW-B

Top safety handrail **LXH**



LXH

Plastic ends **LXS**



LXS